



| Product Code | Adhesive | Thickness | Description | Use | Image |
|---------------------------|------------------|-----------|--|--|-------|
| DOUBLE SIDED TAPES | | | | | |
| C2 | Emulsion Acrylic | .3mm | A double sided carpet tape with an emulsion acrylic adhesive. Made from a permanent high strength adhesive and can be hand torn. | For use on carpet and flexible floor coverings. Also suitable for stereo and block mounting in the printing industry, mounting signs, notices and large nameplates. | |
| C2A | Solvent Rubber | .38mm | C2A is a thick double sided rubber based adhesive, designed for flooring carpet and general laminating to uneven surfaces. Aggressive tack which adheres well in moist conditions. | Suitable for permanent laying of carpet | |
| C3 | Solvent Acrylic | .125mm | A non woven, bonded rayon fibre tape. This product features very high initial tack by using the latest in adhesive technology. Due to its unique construction this tape is a viable alternative to transfer adhesives. Suitable for plastics with easy liner removal and excellent holding properties. Automotive approval HN1555. | Ideal for mounting of various plastics and name plates. This product has many uses in general industry including foam lamination and paper splicing. | |
| C7B | Hot Melt | .088mm | Biorientated PP-film with a clear synthetic rubber adhesive and bisilicized paper liner. Excellent tack with good adhesion. | Suitable for lamination onto polyester and polyether foams, advertisements, envelopes, and computer listing paper. Also suitable for mounting of abrasive pads onto polishing machines. | |
| C57 | Emulsion Acrylic | .11mm | An economical and high performance modified emulsion acrylic adhesive system with a non woven tissue carrier and bisilicized paper liner. Exhibits high initial tack with excellent bonding to uneven surfaces and porous substrates and is weather resistant and UV stable. | This product is useful for various mounting applications, foam lamination, gasketing, paper splicing. Also suitable in the manufacture of corrugated board, bituminised soundproofing on truck and building panels | |
| C127 | Acrylic | .130mm | An economical and high performance solvent acrylic adhesive system with a tissue paper carrier and white lassine paper interliner. This double sided tape exhibits high initial tack with excellent bonding to uneven surfaces. Can be torn by hand and is clean and easy to use. | Uses include various mounting applications. Suitable for foam lamination, paper splicing and automotive applications. Also used in the shoe and leather industry. | |
| C26 | Emulsion Acrylic | 1.03mm | A double sided white PE closed cell foam tape with a high strength adhesion. PE foam with minimal compression ability and has excellent resistance to plasticisers, oils, UV light and humidity. Also available with solvent adhesive (C26X). | Suitable for moulded plastic, plastic signs, reflectors, floor and wall paneling, trim moulding and nameplate applications. | |
| C63 | Butyl Rubber | 1.0mm | An aggressive, self amalgamating, weather proof butyl rubber tape. High instant tack with high tensile strength. Resistant to moisture making it ideal for use indoors and outdoors. | Can be used for sealing subconcrete membranes in critical areas, dam liners and grain bunkers. Suitable for applications where a strong, long lasting waterproof seal is required. | |
| SINGLE SIDED TAPES | | | | | |
| C18 | Synthetic Rubber | .2mm | A clear mono directional tape with high tensile strength. (Also available C18B) | Ideal for bundling and packaging where high loads are involved. Also for useful for high strength strapping and carton sealing. | |
| C24 | Solvent Rubber | .22mm | A premium polyethylene mesh cloth tape with a quality natural rubber adhesive. This tape provides good workability and vapour resistance. Can be used indoors and outdoors with excellent resistance to moisture. Easy to tear and will not twist or curl. | Higher grade tape for use in industrial situations, carpet, plumbing and asbestos applications. Can be used for waterproof packaging, patching, sealing, holding, colour coding, seaming, splicing, protecting and bundling. | |



| Product Code | Adhesive | Thickness | Description | Use | Image |
|--|-----------------|------------------|---|--|--|
| SINGLE SIDED TAPES (cont.) | | | | | |
| C8C | Solvent Rubber | .3mm | Made from an aggressive natural rubber solvent based adhesive. This tape conforms well to surface contours and has good impact resistance and high wet grab. Also available in acrylic and hot melt adhesive. | Can be used for industrial grade packing, carton sealing and bundling. Available in brown and clear. | |
| C16H | Hot Melt | .13mm | An economical masking tape which resists water, solvents and oils. Also available, Premium Masking Tape (C16P). | Ideal for general purpose masking and packaging tasks as well as sealing and bundling. | |
| C25A | Natural Rubber | .368mm | An extra heavy duty (US Gaffa) polyethylene coated cloth tape. Waterproof and conforms well to irregular surfaces. Known for its superior strength and clean removal qualities. | Can be used in a wide variety of applications including duct sealing. | |
| C28X | Solvent Acrylic | .145mm | All weather tape with a clear UV stable polyethylene backing. Chemical and water resistant and will withstand prolonged exposure to sunlight. | Designed for seaming and repairing PE or PVC film such as pool and greenhouse covers. Also useful for container sealing whenever a waterproof conformable seal is essential. | |
| FOAM TAPES - Closed & Open Cell | | | | | |
| Closed Cell | C21 | Solvent Acrylic | 2-12mm | A high quality closed cell polyethylene foam tape with C3 solvent acrylic system. Ideal for external applications. Resistant to weather and suitable for die-cutting. | This product has many industrial uses where hermetic sealing of doors, hatches and access doors and panels is required. Ideally used where frequent opening and closing may be required. |
| Closed Cell | C22 | Hot Melt Solvent | 2-12mm | This closed cell polyethylene foam is made of clear synthetic rubber adhesive giving it excellent tack and good adhesion. | Industrial use, hermetically sealing of doors, hatches and access panels. Can be die cut to customer's specific requirements. |
| Closed Cell | C23A | Acrylic | 2-12mm | An economical, high performance foam tape made up of a clear modified emulsion acrylic adhesive system. | This product is ideal for gasketing, foam lamination and paper splicing. |
| Open Cell | C10 | Acrylic | 3-12mm | A quality soft open cell polyester foam tape with high initial tack. | Perfect for general industrial use for cushioning, sealing, sound and dust proofing. Can be die cut to customer's specific requirements. |
| Open Cell | C11A | Acrylic | 3-12mm | A quality soft open cell polyester foam tape with an emulsion acrylic adhesive system. Features an aggressive adhesive system with high initial tack. | This product has many industrial uses as a low compression light and dust sealant. |
| Open Cell | C15A | Hot Melt | 3-12mm | A quality soft open cell polyester foam tape with a synthetic rubber adhesive | This product has many industrial uses as a low compression light and dust sealant. |
| FELT TAPES | | | | | |
| C31 | Solvent Acrylic | 1-3mm | Black or green high quality wool mix felt tape with a solvent acrylic system. Can be die cut. Also available with other adhesive grades. | Provides anti-squeek and rattle protection for automotive and industrial uses. Protects from scratching and can be used as cushioning for trophies, ornaments, furniture, etc. | |
| C56B | Hot Melt | 2.7mm | A non woven polyester needle felt with a printable surface. | Various industrial uses including padding felt, base for picnic rugs, sub-irrigation and greenhouse framework. | |
| PRINTED TAPES | | | | | |
| C8P | Hot Melt | .035mm | Printable with up to three colours, this product is produced from white film and a clear adhesive giving it superior whiteness. Adheres well to a variety of surfaces. Available in 3 colours, white, yellow and clear. | Used for customer promotions as well as for factory labelling. Suitable for hand dispensers and automatic case sealers. | |
| C17P | Solvent Rubber | .035mm | Custom printed PVC tape. Available in 3 colours on clear, coloured or white PVC. Also available, customer printed PP tape (C8P). | Used for product identification and carton sealing. | |
| C17PPL | Solvent Rubber | 0.68mm | Custom printed, laminated and perforated labels in roll form. Printed as per C17P over-laminated with clear polypropylene. | Used for product identification and general labelling. Can be written on using solvent marker pen. | |

Hot Melt:
Heated blend of synthetic rubber and resin.

Emulsion Acrylic:
Pure and modified emulsion acrylic.

Solvent Acrylic:
Pure and modified solvent rubber.

Solvent Rubber:
Solvent based natural rubber.



| | Tack | Adhesion | Temp. Resistance | UV Resistance | Aging Resistance | Plasticiser Resistance | |
|------------------|------|----------|------------------|---------------|------------------|------------------------|---------------|
| Hot Melt | ★★★ | ★★ | ★ | ★ | ★★ | ★★ | |
| Emulsion Acrylic | ★★ | ★★★★ | ★★★★ | ★★★★ | ★★★★ | ★★★★ | Excellent ★★★ |
| Solvent Acrylic | ★★ | ★★★★ | ★★★★ | ★★ | ★★ | ★★ | Good ★★ |
| Solvent Rubber | ★★★★ | ★★ | ★★ | ★★ | ★★ | ★★ | Poor ★ |